

ST HELENS CUSTOMER TECHNICAL SPECIFICATION

Version Number: 1

PRODUCT INFORMATION			
Product Code:	1037925	Product Description:	INF HP6 BRN
Product Group:	INF HOTPACS	Tray Size:	HP6
		SAP CODE	N/A
Material:	Extruded Polypropylene		
Outer EAN Code:	5021306100404	Inner EAN Code:	N/A
Total Product Weight (g) (±8%):	8.54	(Total product weight includes Tray, Elite glue, Pad and Adhesive)	

TRAY	PAD	PACK	PALLET
Colour: White	Pad Colour: N/A	Stick Count: 110	Packs per Layer: 4 + 2
Colour Reference: No colour ref	Pad Weight (g) (±10%): 0.00	Sticks per Pack: 2	Layers per Pallet: 10+3
Tray Weight (g) (±8%): 8.54	Adhesive Weight (g) (±10%): 0.00	Pack Quantity (ave.): 220	Pallet Quantity (ave.): 10120
Length (mm) (±1): 150.00	Length (mm) (±2): N/A	Nett Weight (g) (±10%): 1878.80	Nett Weight (Kg) (±10%): 86.42
Width (mm) (±1): 150.00	Width (mm) (±2): N/A	Gross Weight (g) (±10%): 1965.49	Gross Weight (Kg) (±10%): 90.41
Height (mm) (±1): 75	Pad Type: N/A	Length (mm) (±10%): 600	Length (mm) (±10): 1500
Diameter (mm) (±1): N/A	Absorbency (H ₂ O) (g) (±10%): N/A	Width (mm) (±10): 620	Width (mm) (±10): 1200
Product Volume (m ³): 0.00000	Pad Material (when present): <i>PE laminated cellulose and acrylic fibres</i>	Height (mm) (±10): 150	Height (mm) (±10): 2100
Absorbency (H ₂ O) (g) (±10%): N/A	Pad Adhesive (when present): <i>Synthetic polymer based hot melt glue</i>	Pack Volume (m ³): 0.0558	Pallet Volume (m ³): 3.7800
Laminate thickness (µ): N/A		Material (inner): MDPE	Pallet Type: Medium
Anti-block agent: Silicon		Material (outer): MDPE	Pallet material: Wood
Adhesive Weight (g) (±10%): 0		Closure: Tape	Card Lid and Base: 0
Box closure type: Single Tab			Card Corner posts: 0
			<i>Pallet Wrap (LLDPE) Stretch</i>

General Usage Instruction:

These trays are for single use only, and can be used for high temperature applications up to 121°C for up to 30 minutes including microwave applications where the contents do not exceed these conditions.

Warning:

N/A

Storage Instruction:

The product should be kept in its original packaging until required. The atmosphere should be maintained to provide good ventilation and ideally at a temperature between 5°C and 30°C. Avoid exposure to heat sources such as hot radiators, direct sunlight, excessive moisture or humidity. Products should be used within 12 months of the delivery date.

Recycling Information:

The packaging can be recovered where facilities exist for recycling or incineration with energy recovery.

Recycled Content:

This product contains no post consumer recycled materials. Process by-products are recycled internally and re-used through the process as raw materials.

Heavy Metals Content:

Heavy Metals Statement

Food Contact Status:

Trays comply with all relevant EU Materials and Articles in contact with Food regulations and directives. Declaration of Compliance and Product Safety Datasheet are available on request.



ST HELENS CUSTOMER TECHNICAL SPECIFICATION

REACH Compliance:

We can confirm that Klöckner Pentaplast is fully aware of the European Community Regulation on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) and our associated responsibilities. A full statement is available on request.

Good Manufacturing Practice:

This product is manufactured in a manner consistent with the aims of Good Manufacturing Practice (GMP).

Allergens:

Allergens - Regulation (EU) No 1169/2011

This product does not contain allergenic substances listed in Annex II of Regulation (EU) No 1169/2011.

Klöckner Pentaplast employees do not use latex gloves, utensils or other latex implements. A full statement is available on request.

Pad Absorption:

It is the responsibility of the user to ensure that the absorbency of the pad is sufficient such that saturation of the pad is avoided.

Barrier Properties:

A supplementary sheet detailing barrier properties is available on request.

Colour Tolerance:

Colour is expressed as a comparison to the Klöckner Pentaplast Colour Standard (referenced above). $\Delta E_{ab} = \pm 4.00$

Black Specks:

Occasional black specks of charred polymer identified in rPET trays and containers. A full statement relating to this issue is available on request.

The information below gives details of the allowable levels of this type of contamination. This specification relates to materials embedded in the plastic that are intrinsic to the manufacturing process, it does not relate to materials extraneous to the manufacturing process or loose particulate of a foreign nature.

Area of particle	Numbers per m ²
0.08 - 0.20mm ²	Maximum 100/m ²
0.20 - 1.00mm ²	Maximum 50/m ²
> 1.00mm ²	None

Traceability Information:


A barcode label is attached to every outer pack. In the event of a complaint please return the barcode label and product samples to Klöckner Pentaplast.



The image shows a barcode label with the following information and callouts:

- Item Code:** 1007221
- Works Order:** 42089
- Bag number:** 3
- Pack quantity:** 144
- Item description:** RPT PE R4C - 80 CLR PAD
- Production date:** 12/09/11
- Shift identification:** C

Name: Duane Coaten

Signature: 

Date of Specification: 20/02/2023

Version Number: 1

Name:

Signature: **Date of Signature:**

This specification is an uncontrolled copy and is valid only on the day of issue. Klöckner Pentaplast reserve the right to amend this specification at any time. Klöckner Pentaplast disclaims liability for all uses that are not expressly designated in this specification.